

## QL-250

# Budget Friendly Wide-Format Desktop Label Printer



Featuring a compact design and software-based user interface, the **QL-250** delivers the superior print quality and high productivity of more expensive systems, at a budget-friendly price. The **QL-250** delivers for moderate production volumes at a low total cost of operation.

- Sharp print resolution up to 1600 dpi
- Print Width up to 8.6"
- User Friendly Interface and Operation
- Designed for Moderate Print Volume

# Technical Specifications

## Operation

<b>Print Technology</b>	Thermal Inkjet
<b>Ink Type</b>	High-Performance Dye ink, (5) individual CMYKK Cartridges
<b>Print Resolution</b>	1600 dpi x 1600 dpi / 1600 dpi x 800 dpi
<b>Print Speed</b>	6 ips (152 mm/sec) @ 1600 dpi x 1600 dpi 12 ips (305 mm/sec) @ 1600 dpi x 800 dpi
<b>Label Size/Print Area</b>	Width: 2.0" (50.8 mm) - 8.6" (218 mm) Length: 2.25" (57.2 mm) - 75" (1904 mm)
<b>Media Sensing</b>	Gap, Reflective (bottom-only), Continuous
<b>Cutter</b>	Approximately 400,000 cuts on paper liner
<b>User Interface</b>	Power, Print/Pause, Cancel/Cut LED Buttons
<b>Connectivity</b>	USB 2.0; 10/100 BaseT Ethernet, RJ-45 connection
<b>Software</b>	Microsoft Windows® 11, 10 64/32-bit Driver CQL Pro® advanced label creation and print management software (one free license included)
<b>Color Matching</b>	ICC Color profile support for qualified media

## Printing Supplies

<b>Ink Cartridges</b>	QuickLabel QL-250 CMYKK Dye cartridges, 250mL
<b>Wiper Module</b>	Approximately 5,000 wipes

## Media

<b>Width</b>	2.125" (54 mm) - 9.0" (228.6 mm)
<b>Length</b>	2.25" (57.2 mm) - 75" (1904 mm)
<b>Thickness</b>	3.9 - 11.8 mil (0.1 mm - 0.3 mm)
<b>Roll Size</b>	10" OD (254 mm), 3" ID (76 mm) core

## Environmental & Physical

<b>Printer Operating</b>	59° F to 95° F (15° C to 35° C), 30% to 90% Relative Humidity (non-condensing)
<b>Printer Storage</b>	23° F to 113° F (-5° C to 50° C), 30% to 90% Relative Humidity (non-condensing)
<b>Ink Storage</b>	32° F to 95° F (0° C to 35° C), 35% to 85% Relative Humidity (non-condensing)
<b>Atmospheric Pressure</b>	1060hPa (795mmHg) - 700hPa (525mmHg)
<b>Power Requirements</b>	100 - 240 VAC 50/60Hz, 2.5A
<b>Power Consumption</b>	Operating: 60W (max) Idle: 30W (max)
<b>Dimensions</b>	Print Unit (only): 21" L x 21" W x 11" H (533 mm x 533 mm x 279 mm) Unwinder/Rewinder: 17" L x 9" W x 11" H (432 mm x 229 mm x 279 mm)
<b>Weight</b>	70 lbs. (31.8 Kg) Print Unit without supplies 17.5 lbs. (7.9 Kg) Unwinder 18.3 lbs. (8.3 Kg) Rewinder
<b>Optional Accessories</b>	RW-250 Unwinder, 10.0" (254 mm) OD Roll (required for roll printing operation)  RW-250 Rewinder, 10.0" (254 mm) OD Roll (optional)

## Warranty

One-Year Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies)

## What's Included

QuickLabel QL-250 printer, AC power cord, USB Cable, Installation Guide

CQL Pro® advanced label creation and print management software (one free license included)

Manufacturer-Direct Sales, Warranty and Service | Unlimited Telephone, Web and E-mail Technical Support

Optional On-Site Setup & Training, Extended Warranty and Support programs available



*The Labels You Want When You Need Them.®*

877-757-7978 | Tel: 401-828-4000 | [info@astronovaproductid.com](mailto:info@astronovaproductid.com) | [www.astronovaproductid.com](http://www.astronovaproductid.com)