

Efficient. New. Basic.

The new HERMA basic

Economic labeller for standard uses



HERMA
Innovation



Efficient. New. Basic.

The new HERMA basic



For low-cost labelling solutions

The HERMA basic redefines the technical benchmark in its class. Its performance and market positioning are both excellent reasons for deciding for the market-leading HERMA technology.

Reliable, rugged and precise with standard applications

The HERMA basic works at a speed of up to 25 m/min: this can be adjusted using the keypad and display. Its integrated controller means there is no need for an additional switch cabinet. Label sizes can be adjusted from 12 x 12 mm to 160 x 400 mm.

Made in Germany, made by HERMA

The HERMA basic has genuine HERMA DNA. The processing quality is the accustomed, familiar high standard expected from HERMA. The HERMA basic is manufactured in the same plant in Germany that produces the globally successful HERMA 400 labeller.

Versatile solution to new challenges

The HERMA basic is fitted with mounting points that are identical to those of the HERMA 400. If special applications or higher speeds are required, it is easy to switch to the more powerful applicators of the HERMA 400 family.



The new HERMA basic

Available label sizes	12 x 12 mm to 160 x 400 mm; single-layer and multi-layer labels with a label thickness of up to 1.5 mm
Max. backing tape width	164 mm
Label roll diameter	300 mm (winding: inward/outward)
Label roll core	Core 76 mm (optional: 40 mm, 45 mm)
Max. speed	Adjustable up to 25 m/min
Label stop accuracy	± 0.8 mm
Clearance	300 mm (suitable for integration in printers e.g. hot foil printers)
Unwinder	Mechanical
Winder	Mechanical (regulated)
Design	Left-hand and right-hand version
Label stop sensor	Forked light barrier for non-transparent labels; optional FS03 sensor can be used for transparent labels
Control panel	Keypad with display; languages available: German, English, French, Spanish
Controller	Integrated in the applicator
IP protection type	IP 40
Power connection values	110 / 240V AC ±10%, 50 / 60 Hz; wide voltage input (automatic adjustment) available power cords: type B NEMA 5-15, 3-pin/ type E+F CEE 7/7
Mounting	Mounting points identical to those of HERMA 400
Label transfer	Adjustable: rigid dispensing plate with brush, roller or spring-mounted roller or optional pneumatic pivot beak
Fault display	Shown in the display
Certification	CE conformity



OZNAČEVANJE IZDELKOV IN EMBALAŽ

Za več informacij se obrnite na podjetje Markpro d.o.o., Celjska cesta 58, 3212 Vojnik
Telefon +386 8 205 80 30 E-poštni naslov info@markpro.si Spletna stran www.markpro.si

HERMA GmbH
Labelling Machines Division
Plochingen Straße 48
73779 Deizisau, Germany

www.herma-labeler.com
www.herma.com
Tel. +49 (0) 711 / 7702-778